

## 冲击电钻

MT80A 10mm(3/8")

MT80B 16mm (5/8")

# 强劲的冲击力，随意调节转速

MT80A:

钻夹头装夹能力 1.5 - 10mm (1/16"-3/8")

二种工作模式:

单钻 / 锤钻



符合人体工程学设计的手柄  
完美适合手型，提供最大的舒适度和操作性。

无段变速开关，转速每分钟  
0 ~ 2900 转可调

MT80B: 钻夹头装夹能力

1.5 - 13 mm (1/16"-1/2")

侧柄

增强工具的操作性



正反转调节杆



 双重绝缘

 无段变速

 正反转

85 

	MT80A	MT80B
额定输入功率	500W	500W
能力	混凝土: 10mm (3/8") 钢材: 10mm (3/8") 木材: 20mm (13/16")	混凝土: 16mm (5/8") 钢材: 13mm (1/2") 木材: 20mm (13/16")
冲击数 (ipm)	0 - 43,500	0 - 43,500
回转数 (rpm)	0-2,900	0-2,900
体积 (长 X 宽 X 高)	254x70x196mm (10"x2-3/4"x7-3/4")	262x70x196mm (10-3/8"x2-3/4"x7-3/4")
净重	1.6kg (3.4lbs)	1.7kg (3.7lbs)
电源线	2.0m (6.6ft)	2.0m (6.6ft)

标准附件  
钻卡键，侧柄