



满足专业人士需要

冲击电钻 HP1630 / HP1631 16 mm (5/8")



照片：HP1631


高性能表现

配有筒型机壳和铝制齿轮箱盖

大功率710W电机



HP1631: 无匙夹头
HP1630: 有匙夹头



坚固的铝制齿轮箱盖

双操作模式：单转/锤转



坚固的筒型机壳



额定输入功率：
710W
同级别产品中功率最高

带有正逆转切换杆的调速控制开关



橡胶软把手
更便于控制、握持更舒适。



照片：HP1631



冲击电钻



双重绝缘



无段变速



正逆转



无匙夹头
(仅限HP1631)



HP1631/ HP1630 16mm (5/8")

85

	HP1630	HP1631
额定输入功率	710W	710W
能力	混凝土：16mm (5/8") 钢材：13mm (1/2") 木材：30mm (1-3/16")	混凝土：16mm (5/8") 钢材：13mm (1/2") 木材：30mm (1-3/16")
冲击数 (ipm)	0-48,000	0-48,000
回转数 (rpm)	0-3,200	0-3,200
尺寸 (L x W x H)	296 x 75 x 204mm (11-5/8" x 2-15/16" x 8")	295 x 75 x 204mm (11-5/8" x 2-15/16" x 8")
净重	1.9kg (4.2lbs)	1.9kg (4.2lbs)
电源线	2.0m (6.6ft)	2.0m (6.6ft)

标准附件 侧手柄、钻卡键 (仅限HP1630)

不同国家或地区的标准附件和规格可能不同。

Makita Corporation

<http://www.makita.com.cn>