



USB适配器 ADP001G



40V Li-ion max

随时速地给手机充电

USB 开关



- 按钮式开关USB 输出开关
(LED 灯绿色时, 表示开关出于开启状态)
- 具有自动关闭功能

二个 USB 端口



ADP01 有二个 A 型 USB 端口,
每个端口都是 5V/2.4A 的输出

腕带孔



※ 图中腕带另售

最大输出电流：2.4A

※ 图片中的电池、USB 数据线、
电动工具、智能手机是另售的

iPhone XR 可以充满电的次数

40Vmax

BL4020	2.8
BL4025	3.5
BL4040	5.6
BL4050F	7.0

充电时间

	快速 充电		DC40RC (191M98-7)	
	DC40RA (191E11-7)			
	DC40RB (191N16-1)			
		BL4020 2.0Ah (191L31-3)	22分钟	30分钟
		BL4025 2.5Ah (191B38-9)	28分钟	38分钟
	BL4040 4.0Ah (191B28-2)	45分钟	67分钟	
	BL4050F 5.0Ah (191L49-4)	50分钟	85分钟	

USB适配器

TWAADP001G

iPhoneXR充满电次数:	使用电池BL4020 / BL4025 / BL4040 / BL4050F: 2.8 / 3.5 / 5.6 / 7.0
USB端口	2 (A type)
最大USB输出电流	一个端口: 2.4Ah 两个端口: 4.8Ah
尺寸(长 x 宽 x 高)	裸机: 96 x 76 x 40 mm (3-3/4 x 3 x 1-9/16") 使用电池 BL4020 / BL4025: 119 x 79 x 88 mm (4-11/16 x 3-1/8 x 3-1/2") 裸机: 0.14 kg (0.3 lbs.) 0.8 - 1.4 kg (1.8 - 3.1 lbs.)
净重	

规格和设计如有变更, 恕不另行通知



牧田(中国)有限公司



微信公众号



抖音号

全国查询电话

www.makita.com.cn

400-928-6517

(接听时间: 8:00-17:00, 节假日除外)